

Doors with thermal insulation

Frame and sash: anodized aluminum

Filling: 40mm PU panels, stucco engraving, limited surface

Equipment: hinges, rubber seals, handle, lock, 3 keys

Additional equipment: windows 680 * 373mm, shutter


Purpose of use: industrial objects, anaries, garages




Standard tones




Stucco grain surface




RAL-7016 / 9010
Anthracite




RAL-9006 / 9010
Silver




RAL-9007 / 9010
Dark silver



RAL-8014 / 9010
Brown




RAL-9010 / 9010
White



RAL-3000 / 9010
Red



RAL-5010 / 9010
Blue



RAL-1021 / 9010
Yellow



Dark oak / 9010




Gold oak / 9010



Mahogany / 9010



RAL-7016 / 9010
Anthracite smooth polygrain



RAL-9016 / 9016
Smooth white

PANEL SPECIFICATION

1. Freon free polyurethane foam, density 42-45 kg/m³
2. Steel sheet 0.5 mm
3. Panel strength on top and bottom side are supported with hardening ribs of 1.0 mm
4. Panel steel sheet is coated with hot dip galvanizing method
5. Polyester priming 10 microns
6. Polyester paint 15 microns
7. Polyester paint 15 microns (according to the RAL tone).
8. Polyethylene film, that protects the door panels to the potential damage during transport and installation.

Products



Sectional overhead gates



Folding gates



High speed



Dock equipment



Riga Door Systems SIA

„Malas”, Vētras, Mārupe LV-2167,
Latvija

Tel: +371 67840085

Mob: +371 26123490, +371 29297341

E-mail: info@rigadoors.lv

www.rigadoors.lv